

CP- VNR-3216

16 Ch. 4K Network Video Recorder



Main Features

- 16 Channel IP Camera Input
- Ultra H.265/H.265/H.264 Video Formats
- Support 4K Resolution Upto 12MP Recording
- 320 Mbps Incoming/ 320Mbps Outgoing Bandwidth
- Support 2 SATA HDDs up to 10TB Each, 3 USB Ports
- Support Multi-brand network cameras
- Mobile Software: Android, iOS
- CMS Software: IVMS



CP- VNR-3216

16 Ch. 4K Network Video Recorder

Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
HDMI/VGA Output
Compression
Recording Resolution
Video Recording
Corridor Mode Screen
Live View/Playback
Capability
Video Display Split
Audio Input
Audio Output
Alarm Input
Alarm Output
Hard Disk
Playback
Interface Ports
Max User Account
Ethernet
Protocols
Power Supply
Power Consumption
Working Temp
Working Humidity
Dimensions
Weight

Specification

Dual-core embedded processor
16 channel
Embedded LINUX
1 channel, RCA
GUI
HDMI: 4K (3840x2160)/60Hz, 4K (3840x2160)/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Ultra H.265/ H.265/ H.264
12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
320 Mbps
3/4/5/7/9/10/12/16
12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
3 x 12MP@25, 4 x 4K@30, 9 x 4MP@25, 16 x 1080p@30
1/4/8/9/16
1 channel, RCA
1 channel, RCA
8 channel
2 channel
2 SATA ports, up to 10TB Each
16 Channel
3 USB Port, 1 RS485
128
2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface
P2P, UPnP, NTP, DHCP, PPPoE, ONVIF conformance: Profile S, Profile G, Profile T
12V DC
≤ 12 W
-10°C ~ + 55°C (+14°F ~ +131°F)
< 90%
380mm × 315mm ×53mm
≤ 2.48 Kg (without HDD)